

Y24 手持式凿岩机

Y24 HAND-HELD ROCK DRILL



使用范围:

- Y24 型手持式凿岩机最适于在中硬或坚硬 (f=8~18) 岩石上干式钻凿向下或倾斜炮孔
- 该机是小型露天采石场、矿山、农田水利、山区筑路等石方工程或大型矿山二次破碎作业的理想机具
- 随机配有透明壳体的 YF200B 型注油器, 提供作业时自动润滑。

Introduction:

- Most suitable for drilling downward and inclined blast-holes in medium hard and hard rock with a hardness of f=8~18:
- An ideal tool for rock drilling operations in small open-pit quarries, mines, water conservancy projects and road building in hilly areas, etc, and for secondary blasting in large mines.
- The incorporation of FY200B Line Oiler with transparent casing provides automatic lubrication during operation during operation.

结构特点:

- 操作机构机重、启动灵活、工作平稳、使用维修方便
- 除保持 YT24 的优良性外, 还增强了吹洗炮孔的能力

Features:

- Grouped control mechanism, quick to start up with "air-on, water-on, air-off" mechanism, easy operation and maintenance.
- In addition to having the excellent performance of YT24, it has stronger flushing power.

使用与维修:

除必须遵循一般凿岩作业的技术安全规程外, 还应特别注意:

- 螺旋母与活塞是左旋螺纹连接, 拆装时要注意旋转方向
- 机器开动前, 要将 FY2008 型注油器注满润滑油严禁无润滑油作业

Operation & Maintenance:



Besides observance of the general safety precautions for rock drilling operations, particular attention should be paid to the following:

- The rifle nut and the piston are left-hand threaded, be careful with the direction of rotation during assembling and disassembling.
- Before starting the direction of rotation during oiler with lube oil, the drill should not be operated without lube oil.

技术规格: Specifications:

机重	Weight	Kg	24
长×宽×高	L×W×H	mm	605 ×485 ×158
凿岩耗气量	Air consumption	l/s	≤53
气管内径	Air hose dia.	mm	19
凿岩频率	Impact frequency	Hz	≥27
钻孔直径	(Bit size)Bore dia.	mm	34~42
钻孔深度	Drilling depth	m	5
钎尾 (六方对边×长度) Shank size (hex. xL)		mm	22×108±1

*气压: 0.4Mpa。

* Air pressure: 0.4Mpa。

FY200B 型注油器技术规格: FY200B Line Oiler Specifications:

储油量	Capacity	ml	200
重量	Weight	kg	1.02